

SMART DESIGN . STRONG PERFORMANCE

# EXTREME OCTOPUS ONE

BALLISTIC PHOTOCHROMIC TACTICAL EYEWEAR



## TEMPLES

 Fully Adjustable  
Anti-Allergic • Non-Slip

## NYLONEXT FRAME

 Flexible  
Lightweight  
Material


## NOSE PAD

 Ergonomic • Adjustable  
Anti-Allergenic

## BALLISTIC LENS

 2.4mm  
Thickness

## LENS COATING

 Micro Glass™  
Anti-Scratch • Anti-Fog

## OPTICAL INSERT

 Clip-On Available  
Prescription Ready

✓ MIL-PRF-32432A APPROVED • EXTREME MILITARY STANDARD

## PRODUCT OVERVIEW

**Extreme** is an Israeli brand with exclusive patents in the development of eyewear, positioning them as the most advanced company in the world in this sector. As the **main supplier to the Israel Police**, Extreme reaffirms its commitment to quality.

The **Octopus One** (MIL-PRF-32432A) combines advanced ballistic protection with adaptive photochromic technology. Designed for elite units, it ensures optimal vision and safety in rapidly changing operational environments, featuring a lightweight NyloNext frame and distortion-free Class 1 optics.

## STANDARD PACKAGE

- Octopus One Frame (NyloNext)
- Ballistic Photochromic Lens
- Hard Shell Protective Case
- Microfiber Cleaning Cloth
- Adjustable Retention Strap
- Manual & Warranty Card

## OPTIONAL

- Optical Clip-On (6027-001)
- Dust Shield Attachment



## TECHNICAL SPECIFICATIONS

### A. FRAME DIMENSIONS

|               |        |
|---------------|--------|
| Lens Width    | 138 mm |
| Lens Height   | 52 mm  |
| Bridge Width  | 20 mm  |
| Temple Length | 129 mm |
| Frame Width   | 138 mm |

### B. WEIGHT

|               |             |
|---------------|-------------|
| Frame Only    | 20 g        |
| Lens (single) | 20 g        |
| <b>Total</b>  | <b>40 g</b> |

### C. LENS SPECIFICATIONS

| Property      | Value       | Details                            | Lens Options  |
|---------------|-------------|------------------------------------|---|
| Material      | PC          | High-impact Polycarbonate          |  <b>6027-020</b><br>Gray Lens      |
| Thickness     | 2.40 mm     | Ballistic rated thickness          |  <b>6027-027</b><br>Clear Lens     |
| Optical Class | Class 1     | Distortion-free optics             |  <b>6027-029PH</b><br>Photochromic |
| Transmission  | 25% - 89%   | Photochromic active range          | <i>All lens types available as replacement parts</i>  |
| Coating       | Multi-layer | Anti-Fog (In) / Anti-Scratch (Out) |   |

## CERTIFICATIONS

### MIL-PRF-32432A

US Military Ballistic

### ANSI Z87.1

High Mass Impact

### EN 166

European Safety

### UV 400

100% UV Protection

## FEATURES & COMPONENTS

### B BALLISTIC PROTECTION

Engineered to withstand high-velocity impacts exceeding standard safety requirements (MIL-STD).



### DUST SHIELD (OPTIONAL)

Foam protection gasket with adjustable elastic strap system for sealing against dust.

### P PHOTOCHROMIC OPTICS

Lenses automatically darken (25%) or lighten (89%) based on UV exposure for seamless transition.



### OPTICAL CLIP-ON (OPTIONAL)

Prescription lens adapter (6027-001). Clips securely behind ballistic lens.

### A ANTI-FOG SYSTEM

Advanced chemical-bonded coating prevents fogging in humid or high-exertion environments.

### F NYLONEXT FRAME

Ultra-lightweight, flexible, and unbreakable frame material designed for extreme durability.